

Desktopové monitory

MULTISYNC E244F



Prioritising user comfort and delivering reliable performance, the E series is a perfect solution for the home office and small to medium sized businesses.

- Cost and time saving operation – based on an intuitive OSD design making set-up simpler.
- Ergonomic Office – full height adjustability (120 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Black and white colour versions – white is considered to reduce the impression of tunnel vision when placed in front of a white background such as office walls.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, protecting users eyes.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

Technické údaje

Technológia obrazovky	VA TFT with W-LED backlight
Pomer šírky k výške obrazovky	16:9
Jas (cd/m ²)	250
Kontrastný pomer	3000:1
Rozstup pixlov (mm V/Š)	0,249
Response Time (typ.) [ms]	6
Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	120
Screen Swivel [°]	-170 - 170
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	541
[AVSpecificationLandscapeDimensionsHeightMm]	501
[AVSpecificationLandscapeDimensionsDepthMm]	233
Prevádzková teplota (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Sieťový pohotovostný režim)
Montáž (VESA/počet bodov/Rozstup v mm)	100 x 100
Zámok Kensington	True
Veľkosť uhlopriečky (palce/cm)	22
Colours [Mio.]	16
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Vertical Frequency [Hz]	50 - 75
Power Supply	Integrated Power Supply

Colour Versions	Predné rámy v čiernej farbe, Zadná časť skrine v čiernej farbe, Predné rámy v bielej farbe, Zadná časť skrine v bielej farbe
Cable Management Plug & Play Audio	True VESA DDC2Bi 1 W + 1 W (vypínateľné), Slúchadlový konektor
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free
Obmedzená záruka výrobcu (roky)	3 roky záruka vrátane záruky na podsvietenie
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	Vyhovuje RoHS
Hmotnosť výrobku bez stojana (kg) Hmotnosť výrobku so stojanom (kg)	4 6
Príslušenstvo	
Shipping Content	Napájací kábel, DisplayPort kábel, Spríevodca nastavením
Digital Analog	DisplayPort, HDMI D-sub 15 pin
Rozmer fazetky (L/P) mm Rozmer fazetky (L) mm	3 17
Optimum Resolution	1920 x 1080 at 60 Hz

