

Desktopové monitory

# Sharp/ NEC MultiSync® E244FL



For driving down costs without compromising quality, the E-series prioritises user comfort and productivity making it an excellent solution for both the home office and for small to medium sized businesses for general office applications.

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

# Technické údaje

Technológia obrazovky	VA TFT with W-LED backlight
Pomer šírky k výške obrazovky	16:9
Jas (cd/m <sup>2</sup> )	250
Kontrastný pomer	1000:1
Zobrazenie farieb	16.77
Doba odozvy v ms (priemer šedá - šedá)	6
Rozstup pixlov (mm V/Š)	0,275
Viewing Angle [°]	178
<hr/>	
Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507
<hr/>	
Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45
<hr/>	
Rozmer fazetky (L/P) mm	1
Rozmer fazetky (H) mm	16
Rozmer fazetky (L) mm	16
<hr/>	
Hmotnosť výrobku bez stojana (kg)	5
Hmotnosť výrobku so stojanom (kg)	8
<hr/>	
Veľkosť uhlopriečky (palce/cm)	24
Veľkosť uhlopriečky (palce/cm)	60
<hr/>	
Spotreba energie v režime Zap. (IEC62087:2012)	13 (Eco Mode 2), 19 (typ.)
Power Supply	Integrated Power Supply
<hr/>	
Special Characteristics	Low Blue Light, Local dimming

Colour Versions	Predné rámcčky v čiernej farbe, Zadná časť skrine v čiernej farbe, Predné rámcčky v bielej farbe, Zadná časť skrine v bielej farbe
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1 W + 1 W (vypínateľné), Slúchadlový konektor
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
Obmedzená záruka výrobcu (roky)	3 roky záruka vrátane záruky na podsvietenie
<hr/>	
Prevádzková teplota (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
<hr/>	
<b>Príslušenstvo</b>	
Shipping Content	DisplayPort kábel, Napájací kábel, Sprievodca nastavením, USB-C kábel
<hr/>	
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	Vyhovuje RoHS, TCO 9.0
<hr/>	
Montáž (VESA/počet bodov/Rozstup v mm)	100 x 100
Zámok Kensington	True
<hr/>	
Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75
<hr/>	
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
<hr/>	
Optimum Resolution	1920 x 1080 at 60 Hz

