

# Sharp E501U

For outstanding projection performance at an impressively low total cost of ownership, the Sharp E501U appeals to cost-conscious users who demand professional reliability.



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- Enjoy a Lower TCO – highest reliability, maintenance free operation, low power consumption and up to 20000 hours life; the Laser light source results in a significantly lower total cost of ownership.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.
- Cost Saving Device Management – save effort whilst administrating all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

# Specifications

## Others

|   |     |
|---|-----|
| <b>Power Requirements: voltage Min. (V)</b>           | 100 |
| <b>Power Requirements: voltage Max. (V)</b>           | 240 |
| <b>Power Consumption: standard, ECO, stand-by (W)</b> | 1   |

## Key Specifications

|                                |   |
|--------------------------------|---|
| <b>Special Characteristics</b> | NaViSet Administrator 2, Carbon Savings Meter |
|--------------------------------|---|

## Accessories

|                         |   |
|-------------------------|---|
| <b>Shipping Content</b> | Power Cable, User Manual, 2 x AAA batteries |
|-------------------------|---|

## Environmental Conditions

|                                     |    |
|-------------------------------------|----|
| <b>Operating Humidity (min) [%]</b> | 20 |
| <b>Operating Humidity (max) [%]</b> | 80 |

## Green Features

|                             |                      |
|-----------------------------|----------------------|
| <b>Ecological Standards</b> | ErP compliant        |
| <b>Ecological Materials</b> | Downloadable manuals |

## Display Module Data

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Native Resolution (Pixels)</b> | 1920 x 1200 (WUXGA) |
| <b>Aspect Ratio</b>               | 16:10:00            |
| <b>Contrast Ratio</b>             | 500000:1            |

## Power Supply and Operating Environment

|  |         |
|--|---------|
| <b>Operating Voltage (ACV)</b>               | 100-240 |
| <b>Frequency (Hz)</b>                        | 50-60   |
| <b>Power Consumption (W) (Operating MAX)</b> | 310     |
| <b>Power Consumption (W) (Standby)</b>       | 0.4     |
| <b>Storage Humidity Min [%]</b>              | 20      |
| <b>Storage Humidity Max [%]</b>              | 80      |

## Additional Features

|                              |               |
|------------------------------|---------------|
| <b>Safety and Ergonomics</b> | RoHS, CE, ErP |
|------------------------------|---------------|

## Projectors

|                           |      |
|---------------------------|------|
| <b>Weight (kg)</b>        | 5    |
| <b>Zoom-Lens (Manual)</b> | True |
| <b>Keystone (manual)</b>  | True |

