

Desktopové monitory

EA241F



Ideal for multi-screen usage with a narrow bezel and sleek look, the EA241F maximises productivity with best in class ergonomics.

- In-demand display size – the popular 23.8" display with Full HD resolution is the perfect size for busy office workspaces.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Energy efficiency – reduce your energy consumption by up to 30% by enabling the built-in Human and Ambient Light Sensors ensuring the display is only powered up according to usage conditions.
- Maximum attention to health and well-being – the ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to
- Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Technické údaje

Technológia obrazovky	IPS TFT with W-LED backlight
Pomer šírky k výške obrazovky	16:9
Jas (cd/m ²)	250
Kontrastný pomer	1000:1
Rozstup pixlov (mm V/Š)	0,275
Response Time (typ.) [ms]	5
Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	150
Screen Swivel [°]	170 - -170
Screen Rotate [°]	0 - 90
[AVSpecificationPortraitDimensionsWidthMm]	319
[AVSpecificationPortraitDimensionsHeightMm]	615
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	319
[AVSpecificationLandscapeDimensionsHeightMm]	615
[AVSpecificationLandscapeDimensionsDepthMm]	250
Energy Efficiency	Energy efficiency class: C, Human sensor, Ambient light sensor, Energy consumption: 11 kWh/1000 h
Ecological Standards	Energy Star 8.0, Vyhovuje ErP, Vyhovuje RoHS, TCO 9.0, WEEE
Príslušenstvo	
Shipping Content	Napájací kábel, Príručka pre nastavenie, DisplayPort kábel, USB kábel, Control Sync kábel, Monitor
Digital	DisplayPort, HDMI, USB ver. 3.1 (2 down / 1 up), DVI-D
Analog	D-sub 15 pin
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Montáž (VESA/počet bodov/Rozstup v mm)	100 x 100

Colour Versions	Predné rámy v čiernej farbe, Zadná časť skrine v čiernej farbe, Predné rámy v bielej farbe, Zadná časť skrine v bielej farbe
Cable Management Plug & Play	True VESA DDC2Bi, DDC2B/2Bi, VESA DDC/CI
Audio	Integrované reproduktory (1 W + 1 W)
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment)
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, UL/C-UL or CSA, TCO 8.0, WEEE, CE, EAC, EnergyStar 8.0, ErP, Flicker-free
Obmedzená záruka výrobcu (roky)	3 roky záruka vrátane záruky na podsvietenie, Voliteľná záruka na nepretržité použitie v 1. až 3. roku od kúpy, Voliteľné predĺženie záruky na 4. až 5. rok od kúpy
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Sieťový pohotovostný režim)
Veľkosť uhlopriečky (palce/cm)	24
Colours [Mio.]	16
Colour Gamuts	72% NTSC, 101.6% sRGB, 75.3% AdobeRGB
Frame Material	Aluminum alloy (front); metal (back)
Power Supply	100-240 V, Internal Power Supply, 0.9 A/0.5 A
Rozmer fazetky (L/P) mm	1
Rozmer fazetky (L) mm	15
Optimum Resolution	1920 x 1080 at 60 Hz

